

Product Data Sheet

Synthetic Blend Motor Oil (SM) Premium Gold

SAE: 10W40
Product Code: 564

OVERVIEW

Synthetic Blend Motor Oil SM provides high quality engine protection under all driving conditions and is specifically formulated to provide extra protection against the harmful effects of city driving, where cars undergo higher stress due to constant stops and starts. **Synthetic Blend Motor Oil SM** low friction formula helps improve gas mileage for long engine life and helps protect against rust, corrosion, startup wear, varnish build-up, and eliminates the need for extra oil additives. It also protects against thermal breakdown which helps prevent stuck rings.

FEATURES / BENEFITS

- Protects engines under all driving conditions, especially city driving
- Lowers friction and improves gas mileage

- Provides longer engine life
- Protects against rust, corrosion and varnish
- Resists thermal break-down

APPLICATIONS

Synthetic Blend Motor Oil SM exceeds the demanding requirements of API SM Service Category.

SPECIFICATION /Suitable for Use Claims

Synthetic Blend Motor Oil SM is also recommended for older engines, where owner's manual calls for API SM, SL, and CF Service Classifications or any combination thereof. Viscosity recommendations vary according to temperature and engine manufacturer.

ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER LUBRICANT OIL FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

PRODUCT CODE	564
SAE GRADE	10W-40
API/ILSAC/ACEA Specifications	SM
Specific Gravity	0.8676
Viscosity, cSt @ 100°C	13.3
Viscosity, cSt @ 40°C	86.0
Viscosity, CCS cP @°C	7000 (-25)
Viscosity Index	172
Pour Point, °C	-33
Flash Point, °C	403

The above test data are average values only. Minor variations which do not affect product performance are to be expected during manufacturing. Specific PDS will be provided upon purchase.